

Universal Campus Cable

(Construction and Electrical Performance as per BT Specification CW1308)

Indoor / Outdoor Cable

PACW/PVC Insulation/Moisture Barrier/HFFR Sheathed



CW1308B Indoor outdoor campus cables

Application

The cable is designed primarily for interconnection between buildings within a telecommunication network where the cable is used both inside the building and outside in ducts between the buildings. The cable replaces the traditional PVC sheathed cable inside the building and the Polyethylene sheathed cable outside, making the need to joint at building entries redundant. The design includes a metallic moisture barrier bonded to the sheath to combat the ingress of moisture vapour and the sheath is a low smoke non-halogenated polymer, which imparts a high degree of flame retardancy to the cable. The cable core is similar to BT Specification CW 1308.

Construction

Twisted pairs in 10 Pair Units. The pair range is 10 – 100.

Product description

Plain annealed solid copper wire; PVC insulation with the required number of pairs assembled in 20 pair units. A polyester tape is applied over the cable core followed by a Polyethylene/Aluminium Laminate moisture barrier, which is

Product description (continued)

bonded to the Low Smoke Non-Halogenated (HFFR) sheath. An optional 1.38mm diameter PVC insulated Earth Wire may be included within the cable core on request.



| Number Pairs | Conductor Diameter (mm) | Minimum Radial Insulation (mm) | Maximum Insulated Diameter (mm) | Unit Size/ Make-up | Minimum Sheath Radial (mm) | Maximum Overall Diameter (mm) | Resistance @ 20°C (ohms/km) | Capacitance Unbalance (pF/500m) |
|--------------|-------------------------|--------------------------------|---------------------------------|--------------------|----------------------------|-------------------------------|-----------------------------|---------------------------------|
| 10 | 0.5 | 0.15 | 0.95 | 10 | 0.60 | 8.3 | 97.8 | 500 |
| 20 | 0.5 | 0.15 | 0.95 | 10 | 0.80 | 10.7 | 97.8 | 500 |
| 30 | 0.5 | 0.15 | 0.95 | 10 | 0.80 | 12.2 | 97.8 | 500 |
| 40 | 0.5 | 0.15 | 0.95 | 10 | 0.90 | 15.0 | 97.8 | 500 |
| 50 | 0.5 | 0.15 | 0.95 | 10 | 1.00 | 17.0 | 97.8 | 500 |
| 60 | 0.5 | 0.15 | 0.95 | 10 | 1.20 | 17.0 | 97.8 | 500 |
| 80 | 0.5 | 0.15 | 0.95 | 10 | 1.20 | 22.5 | 97.8 | 500 |
| 100 | 0.5 | 0.15 | 0.95 | 10 | 1.50 | 27.0 | 97.8 | 500 |
| 160 | 0.5 | 0.15 | 0.95 | 10 | 1.70 | 30.0 | 97.8 | 500 |
| 200 | 0.5 | 0.15 | 0.95 | 10 | 1.85 | 32.0 | 97.8 | 500 |
| 320 | 0.5 | 0.15 | 0.95 | 10 | 2.2 | 39.5 | 97.8 | 500 |
| 10(+E) | 0.5 | 0.15 | 0.95 | 10 | 0.60 | 8.6 | 97.8 | 500 |
| 20(+E) | 0.5 | 0.15 | 0.95 | 10 | 0.70 | 12.0 | 97.8 | 500 |
| 30(+E) | 0.5 | 0.15 | 0.95 | 10 | 0.80 | 12.2 | 97.8 | 500 |
| 40(+E) | 0.5 | 0.15 | 0.95 | 10 | 0.90 | 15.0 | 97.8 | 500 |
| 50(+E) | 0.5 | 0.15 | 0.95 | 10 | 1.10 | 18.0 | 97.8 | 500 |
| 80(+E) | 0.5 | 0.15 | 0.95 | 10 | 1.20 | 22.5 | 97.8 | 500 |
| 100(+E) | 0.5 | 0.15 | 0.95 | 10 | 1.50 | 27.0 | 97.8 | 500 |
| 160(+E) | 0.5 | 0.15 | 0.95 | 10 | 1.70 | 30.3 | 97.8 | 500 |
| 200(+E) | 0.5 | 0.15 | 0.95 | 10 | 1.85 | 32.0 | 97.8 | 500 |
| 320(+E) | 0.5 | 0.15 | 0.95 | 10 | 2.2 | 39.5 | 97.8 | 500 |

Note: The items indicated as (+E) in the table above are available with or without an earth-wire. If an earth-wire is included, it consists of a 1.38mm solid copper conductor (maximum resistance 12.4 ohms/km), insulated with Cream PVC to a nominal 2.7mm.

Insulation resistance

Insulation resistance measurements shall be made with not less than 500 volts D.C. After steady electrification for one minute the insulation resistance measured between each conductor and the remaining conductors connected together shall be not less than 50 megohms per 1000 metres at 20°C.

Colour scheme for pairs

| Cabling Element No. | a-wire | b-wire | Cabling Element No. | a-wire | b-wire |
|---------------------|--------------|--------------|---------------------|---------------|---------------|
| 1 | WHITE-Blue | BLUE-White | 11 | BLACK-Blue | BLUE-Black |
| 2 | WHITE-Orange | ORANGE-White | 12 | BLACK-Orange | ORANGE-Black |
| 3 | WHITE-Green | GREEN-White | 13 | BLACK-Green | GREEN-Black |
| 4 | WHITE-Brown | BROWN-White | 14 | BLACK-Brown | BROWN-Black |
| 5 | WHITE-Grey | GREY-White | 15 | BLACK-Grey | GREY-Black |
| 6 | RED-Blue | BLUE-Red | 16 | YELLOW-Blue | BLUE-Yellow |
| 7 | RED-Orange | ORANGE-Red | 17 | YELLOW-Orange | ORANGE-Yellow |
| 8 | RED-Green | GREEN-Red | 18 | YELLOW-Green | GREEN-Yellow |
| 9 | RED-Brown | BROWN-Red | 19 | YELLOW-Brown | BROWN-Yellow |
| 10 | RED-Grey | GREY-Red | 20 | YELLOW-Grey | GREY-Yellow |

Note 1: Uppercase letters indicate the base, solid colour of insulation, and the lower case indicates ink bands applied onto the base colour.

Make-up & unit identification colours – 20 pair unit

| Pair Size | 10 Pair | 20 Pair | 40 Pair | 50 Pair | 80 Pair | 100 Pair | 160 Pair | 200 Pair | 320 Pair |
|-----------|------------------------------|---------|---------|---------|---------|----------|----------|----------|----------|
| | Number of Units | | | | | | | | |
| Centre | ½ | 1 | 4 x ½ | 5 x ½ | 1 | 1 | 4 x ½ | 4 x ½ | 1 |
| 1st Layer | | | | | 6 x ½ | 8 x ½ | 6 | 8 | 5 |
| 2nd Layer | | | | | | ***** | | | 10 |
| Unit No. | Colours of Unit Binder Tapes | | | | | | | | |
| 1 | Orange | Orange | Orange | Orange | Orange | Orange | Orange | Orange | Orange |
| 2 | | | Green | Natural | Orange | Orange | Green | Green | Orange |
| 3 | | | | Green* | Natural | Natural | Orange | Orange | Natural |
| 4 | | | | | Green | Natural | Natural | Natural | Natural |
| 5 | | | | | | Green | Natural | Natural | Natural |
| 6 | | | | | | | Natural | Natural | Green |
| 7 | | | | | | | Natural | Natural | Orange |
| 8 | | | | | | | Green | Natural | Natural |
| 9 | | | | | | | | Natural | Natural |
| 10 | | | | | | | | Green | Natural |
| 11-15 | | | | | | | | | Natural |
| 16 | | | | | | | | | Green |

Note 1: ½ refers to sub-units of 10 Pairs. * The Green colour lapping shall be applied to the last ½ unit. ***** At the manufacturer's discretion the first layer may be 4 x 1. Alternatively the centre layer may be 5 x 1 in which case the Unit lappings shall be coloured Orange, 3 x Natural, Green.



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.

Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited