

# BCC Data-Tec™ - Networking Cable - U/UTP

4 Pair Cat 6A U/FTP Cable - B2ca-s1a, d0, a1

B2ca-s1a, d0, a1  
DoP: BCC1011



## Applications

Suitable for internal use of Local Area Networks and Analogue & Digital video applications, supporting Gigabit Ethernet and POE.

## Category

6 Data Cables

## Standard References

ANSI/TIA-568-C.2  
ISO/IEC 11801 2ND edition  
EN50173-1 & EN50288-10-1  
EN 50575:2014/A1:2016  
IEC 60754-1&2  
IEC 61034-1  
RoHS 2002/95/EC

## Design

- 1. Conductor**  
Solid annealed copper
- 2. Insulation**  
Pair 1: WHITE-Blue/Blue  
Pair 2: WHITE-Orange/Orange  
Pair 3: WHITE-Green/Green  
Pair 4: WHITE-Brown/Brown

## 3. Individual Pair Screening

Al Foil

## 4. Cross member

Polyethylene

## 5. Drain Wire

Tinned Copper

## 6. Ripcord

Nylon

## 7. Sheath

LSZH - Orange

## Standard Put Up Length

305 metres



## Physical Characteristics

Conductor Diameter Nom. (mm)	Insulation Diameter Nom. (mm)	Overall Diameter Nom. (mm)	Cable Weight Nom. (Kg/Km)	Temperature Range (°C)	Min. Bend Radius (install) (mm)
23 AWG	1.35 (±0.2)	7.8 (±0.5)	50	-10 ~ +60	8 X OD

## Electrical Characteristics at 20°C (part 1)

Impedance (Ω)	Max. Conductor DC Resistance (Ω/km)	Mutual Capacitance at 1KHz (nF/100m)	NVP (%)	Min. Insulation Resistance (MΩ*km)	Max. Resistance Unbalance (%)
100±15 (1MHz to 100MHz) 100±22 (300MHz to 500MHz)	93.8	5.6	65	5000	2.5

## Electrical Characteristics at 20°C (part 2)

Frequency (MHz)	Nominal Attenuation (dB/100m)	Minimum NEXT (dB)	Minimum PSNEXT (dB)	Minimum ELFEXT (dB)	Minimum PSELFEXT (dB)	Min. Return Loss (dB)	Maximum SKEW (ns/100m)
1	2.0	75.3	72.3	68.0	65.0	20.0	45
4	3.7	66.3	63.3	56.0	53.0	23.0	45
10	5.9	60.3	57.3	48.0	45.0	25.0	45
16	7.4	57.2	54.2	43.9	40.9	25.0	45
20	8.3	55.8	52.8	42.0	39.0	25.0	45
31.25	10.4	52.9	49.9	38.1	35.1	23.6	45
62.5	14.9	48.4	45.4	32.1	29.1	21.5	45
100	19.0	45.3	42.3	28.0	25.0	20.1	45
200	27.5	40.8	37.8	22.0	19.0	18.0	45
250	31.0	39.3	36.3	20.0	17.0	17.3	45
300	34.2	38.1	35.1	18.5	15.5	17.3	45
500	45.3	34.8	31.8	14.0	11.0	17.3	45



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: [www.britishcablescompany.com](http://www.britishcablescompany.com) | Email: [info@britishcables.com](mailto:info@britishcables.com)

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.

Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited