

BCC BMS-Tec™ - Low Capacitance RS-485 Computer Cables

1 – 2 – 3 or 4 pairs

AWG 22 and 24, Flexible Tinned Copper, Overall Screen, PVC Sheath

BCC Part No: C1080 – C1295 – C1296 – C1297 -C1189 – C1190 – C1191– C1192



Applications

Building Management Systems (BMS), Access Control, Instrumentation

Sector

BCC BMS-TEC™

Standard References

IEC 60332-1
RoHS directives
(BS)EN 50290

Design

1. Conductor

Tinned Copper wire, flexible

2. Insulation

Foam or solid PE
Core 1: White with blue stripe
Core 2: Blue with white stripe
Core 3: White with orange stripe
Core 4: Orange with white stripe
Core 5: White with green stripe
Core 6: Green with white stripe
Core 7: White with brown stripe
Core 8: Brown with white stripe

3. Cabling

Pair 1: core 1 x core 2
Pair 2: core 3 x core 4
Pair 3: core 5 x core 6
Pair 4: core 6 x core 8

4. Screen

Aluminium/Polyester 100% Coverage

5. Braid

Tinned Copper Coverage
(See below table)

6. Outer Screen Drain Wire

Tinned Copper
24AWG (7 x 32)

7. Ripcord

8. Sheath Material

Polyvinyl Chloride (PVC)

Standard Put Up Length

305 or 500 metres



Physical Characteristics

BCC Part Number	Unit	C1080	C1295	C1296	C1297	C1189	C1190	C1191	C1192
No of pairs		1	2	3	4	1	2	3	4
Conductor Gauge	AWG	22	22	22	22	24	24	24	24
Conductor configuration	AWG	7 x 30	7 x 30	7 x 30	7 x 30	7 x 32	7 x 32	7 x 32	7 x 32
Insulation material		FPE	FPE	FPE	FPE	PE	PE	PE	PE
Nom. Radial Thickness Insulation	mm	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
Coverage braid	%	65	65	65	65	90	90	90	90
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8
Nom. Overall Diameter	mm	6.1	9.1	10.5	11.4	5.9	8.5	9.0	9.9

Electrical Characteristics

BCC Part Number	Unit	C1080	C1295	C1296	C1297	C1189	C1190	C1191	C1192
No of pairs		1	2	3	4	1	2	3	4
Max. DC Resistance Conductor	Ω/km	57.4	57.4	57.4	57.4	88	88	88	88
Max. DC Resistance Screen	Ω/km	20	20	20	20	15	15	15	15
Nominal Impedance	Ω	120	120	120	120	120	120	120	120
Capacitance core to core	pF/m	36	37	38	38	41	41	41	41
Capacitance core to rest	pF/m	69	69	69	69	90	80	75	75
Nom. Attenuation at 1 MHz	dB/100m	1.65	1.65	1.65	1.65	0.6	0.6	0.6	0.6
Max. Recom. Current @ 25°C	Amps	2.7	2.7	2.7	2.7	2.1	2.1	1.54	1.54
Max. Operating Voltage	Vrms	300	300	300	300	300	300	300	300

Miscellaneous

BCC Part Number	Unit	C1080	C1295	C1296	C1297	C1189	C1190	C1191	C1192
No of pairs		1	2	3	4	1	2	3	4
Max. Pulling Tension	N	265	355	400	445	320	385	460	485
Min. Bend Radius (install)	mm	60	90	95	105	60	85	90	100
Nominal Cable Weight	kg/km	63.7	75.6	97	119.1	49	80.5	92.6	114.4
Operating Temperature	°C	-25 / +75							



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.
Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited