

BCC BMS-Tec™ - Cables for EIA RS-232 Applications

1 – 2 – 3 – 4 – 5 - 6 – 7 or 8 pairs

24AWG (7 x 32), Flexible Tinned Copper, Overall Screen, HFFR Sheath

BCC Part No: C1441 – C1442 – C1443- C1444 – C1445 – C1446 – C1447 – C1448



BRITISH CABLES COMPANY

Applications

Building Management Systems (BMS), Access Control, Instrumentation

Sector

BCC BMS-TEC™

Standard References

IEC 60332-1
IEC 60332-3-24
IEC 61034
RoHS directives (BS)EN 50290

Design

1. Conductor

N x 2 x Tinned Copper wire, 24AWG flexible (7x32)

2. Insulation

Low Smoke Zero Halogen(HFFR)
Pair 1: Black & Red
Pair 2: Black & White
Pair 3: Black & Green
Pair 4: Black & Blue
Pair 5: Black & Yellow
Pair 6: Black & Brown
Pair 7: Black & Orange
Pair 8: Red & White

3. Drain Wire

24 AWG (7 x 32) Tinned Copper

4. Screen

Aluminium/Polyester
100% Coverage

5. Sheath Material

Low Smoke Zero Halogen (HFFR)
Colour: Violet

Standard Put Up Length

305 metres



Physical Characteristics

BCC Part Number	Unit	C1441	C1442	C1443	C1444	C1445	C1446	C1447	C1448
Number of pairs		1	2	3	4	5	6	7	8
Nom. Diameter Conductor	mm	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
Nom. Radial Thickness Insulation	mm	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.6	0.6	0.4	0.4	0.4
Nom. Overall Diameter	mm	4.0	5.6	5.9	6.7	7.3	7.4	7.5	8.3

Electrical Characteristics

BCC Part Number	Unit	C1441	C1442	C1443	C1444	C1445	C1446	C1447	C1448
Number of pairs		1	2	3	4	5	6	7	8
Max. DC Resistance Conductor	Ω/km	88	88	88	88	88	88	88	88
Max. DC Resistance Screen	Ω/km	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4
Nominal Impedance	Ω	75	75	75	75	75	75	75	75
Capacitance core to core	pF/m	95	55	55	60	60	60	60	60
Capacitance core to other cores.+screen	pF/m	275	122	122	130	130	130	130	130
Nominal Inductance	μH/m	0.62	0.62	0.62	0.62	0.62	0.62	0.62	0.5
Nominal Velocity of Propagation	%	60	60	60	60	60	60	60	60
Max. Recommen. Current @ 25°C	Amps	1.76	1.76	1.76	1.5	1.5	1.1	1.1	1.1
Max. Operating Voltage	Vrms	300	300	300	300	300	300	300	300

Miscellaneous

BCC Part Number	Unit	C1441	C1442	C1443	C1444	C1445	C1446	C1447	C1448
Number of pairs		1	2	3	4	5	6	7	8
Max. Recommend. Pulling Tension	N	45	90	135	180	225	270	315	360
Min. Bend Radius (install)	mm	40	56	59	67	73	74	75	83
Nominal Cable Weight	kg/km	18	28	39	48	57	65	73	85
Operating Temperature	°C	-25 / +75							



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur. Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited