

BCC BMS-Tec™ - Multi Conductor Cables

2 – 3 – 4 – 6 or 8 Cores

16AWG (19x29), Flexible Bare Copper, Overall Screen, HFFR Sheath

BCC Part No: C1711 – C1713 – C1715 – C1717 – C1719



BRITISH CABLES COMPANY

Applications

Screened Multi-Conductor cables suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

Sector

BCC BMS-TEC™

Standard References

(BS) EN 50290-2
IEC 60754-1 & 2
IEC 61034
IEC 60332-3C
RoHS directives

Design

1. Conductor

N x Bare Copper wire,
16AWG flexible

2. Insulation

Polyolefin
Core 1: Black
Core 2: Red
Core 3: White
Core 4: Green
Core 5: Brown
Core 6: Blue
Core 7: Orange
Core 8: Yellow

3. Drain Wire

24 AWG (7 x 32) Tinned Copper

4. Screen

Aluminium/Polyester 100% Coverage

5. Ripcord

6. Sheath Material

Flame-Retardant
Halogen Free (HFFR)
Standard colour: Violet

Standard Put Up Length

305 metres



Physical Characteristics

| BCC Part Number | Unit | C1711 | C1713 | C1715 | C1717 | C1719 |
|----------------------------------|------|-------|-------|-------|-------|-------|
| No of cores x 16AWG (19 x 29) | | 2 | 3 | 4 | 6 | 8 |
| Nom. Diameter Conductor | mm | 1.4 | 1.4 | 1.4 | 1.4 | 1.4 |
| Nom. Radial Thickness Insulation | mm | 0.25 | 0.25 | 0.25 | 0.25 | 0.25 |
| Nom. Radial Thickness Sheath | mm | 0.8 | 0.8 | 0.8 | 0.8 | 0.8 |
| Nom. Overall Diameter | mm | 5.5 | 5.8 | 6.3 | 7.4 | 8.0 |

Electrical Characteristics

| BCC Part Number | Unit | C1711 | C1713 | C1715 | C1717 | C1719 |
|------------------------------------|------|-------|-------|-------|-------|-------|
| No of cores x 16AWG (19 x 29) | | 2 | 3 | 4 | 6 | 8 |
| Max. DC Resistance Conductor | Ω/km | 15.47 | 15.47 | 15.47 | 15.47 | 15.47 |
| Max. DC Resistance Screen | Ω/km | 78.5 | 78.5 | 78.5 | 78.5 | 78.5 |
| Capacitance conductor to conductor | pF/m | 170 | 152 | 165 | 165 | 165 |
| Nominal Inductance | µH/m | 0.5 | 0.5 | 0.5 | 0.5 | 0.5 |
| Max. Recommended Current at 25°C | Amps | 6.25 | 6.25 | 5 | 4.35 | 4.35 |
| Max. Operating Voltage | Vrms | 300 | 300 | 300 | 300 | 300 |

Miscellaneous

| BCC Part Number | Unit | C1711 | C1713 | C1715 | C1717 | C1719 |
|----------------------------------|-------|-------|-------|-----------|-------|-------|
| No of cores x 16AWG (19 x 29) | | 2 | 3 | 4 | 6 | 8 |
| Operating Temperature | °C | | | -25 / +75 | | |
| Max. Recommended Pulling Tension | N | 260 | 390 | 520 | 780 | 1040 |
| Min. Bend Radius (install) | mm | 55 | 58 | 63 | 74 | 80 |
| Nominal Cable Weight | kg/km | 45.4 | 59.2 | 73.6 | 102.6 | 130.4 |



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.
Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited