

# BCC BMS-Tec™ - Multi Conductor Cables

2 – 3 – 4 – 6 – 7or 8 Cores

18AWG (7 x 26), Flexible Bare Copper, Overall Screen, PVC Sheath

BCC Part No: C1013 – C1015 – C1017 - C1211 – C1239 - C1258



## Applications

Screened Multi-Conductor cable suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

## Sector

BCC BMS-TEC™

## Standard References

(BS) EN 50290-2  
IEC 60332-1  
RoHS directives

## Design

### 1. Conductor

N x Bare Copper wire,  
18AWG flexible

### 2. Insulation

Polyolefin  
Core 1: Black  
Core 2: Red  
Core 3: White  
Core 4: Green  
Core 5: Brown  
Core 6: Blue  
Core 7: Orange  
Core 8: Yellow

### 3. Drain Wire

24 AWG (7 x 32) Tinned Copper

### 4. Ripcord

### 5. Screen

Aluminium/Polyester  
100% Coverage

### 6. Sheath Material

Flame-Retardant  
Polyvinyl Chloride (PVC)  
Standard colour: Grey

### Standard Put Up Length

305 metres



## Physical Characteristics

BCC Part Number	Unit	C1013	C1015	C1017	C1211	C1239	C1258
No of cores x 18AWG (7 x 26)		2	3	4	6	7	8
Nom. Diameter Conductor	mm	1.2	1.2	1.2	1.2	1.2	1.2
Nom. Radial Thickness Insulation	mm	0.2	0.2	0.2	0.2	0.2	0.2
Nom. Radial Thickness Sheath	mm	0.4	0.4	0.4	0.4	0.4	0.4
Nom. Overall Diameter	mm	4.0	4.2	4.6	5.75	5.9	6.4

## Electrical Characteristics

BCC Part Number	Unit	C1013	C1015	C1017	C1211	C1239	C1258
No of cores x 18AWG (7 x 26)		2	3	4	6	7	8
Max. DC Resistance Conductor	Ω/km	20.58	20.58	20.58	20.58	20.58	20.58
Max. DC Resistance Screen	Ω/km	78.5	78.5	78.5	78.5	78.5	78.5
Capacitance conductor to conductor	pF/m	120	129	105	95	80	75
Capacitance cond. To other cond.+screen	pF/m	225	230	190	190	175	176
Nominal Inductance	μH/m	0.5	0.5	0.5	0.5	0.5	0.5
Max. Recommended Current at 25°C	Amps	5	5	4	3.5	3.5	3.5
Max. Operating Voltage	Vrms	300	300	300	300	300	300

## Miscellaneous

BCC Part Number	Unit	C1013	C1015	C1017	C1211	C1239	C1258
No of cores x 18AWG (7 x 26)		2	3	4	6	7	8
Operating Temperature	°C	-25 / +75					
Max. Recommended Pulling Tension	N	200	299	399	600	620	797
Min. Bend Radius (install)	mm	40	42	46	58	60	60
Nominal Cable Weight	kg/km	29.6 3	9.2	49.4	70.9	79	89.5



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: [www.britishcablescompany.com](http://www.britishcablescompany.com) | Email: [info@britishcables.com](mailto:info@britishcables.com)

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur. Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited