

BCC BMS-Tec™ - Multi Conductor Cables

2 – 3 – 4 – 6 or 8 Cores

20AWG (7x28), Flexible Bare Copper, Unscreened, HFFR Sheath

BCC Part No: C1732 – C1734 – C1736 – C1738 – C1740



BRITISH CABLES COMPANY

Applications

Multi-Conductor cables suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

Sector

BCC BMS-TEC™

Standard References

(BS) EN 50290-2
IEC 60754-1 & 2
IEC 61034
IEC 60332-3C
RoHS directives

Design

1. Conductor

N x Bare Copper wire,
20AWG flexible

2. Insulation

Polyolefin
Core 1: Black
Core 2: Red
Core 3: White
Core 4: Green
Core 5: Brown
Core 6: Blue
Core 7: Orange
Core 8: Yellow

3. Ripcord

4. Sheath Material

Flame-Retardant
Halogen Free (HFFR)
Standard colour: Violet

Standard Put Up Length

305 metres



Physical Characteristics

BCC Part Number	Unit	C1732	C1734	C1736	C1738	C1740
No of cores x 20AWG (7 x 28)		2	3	4	6	8
Nom. Diameter Conductor	mm	1.0	1.0	1.0	1.0	1.0
Nom. Radial Thickness Insulation	mm	0.25	0.25	0.25	0.25	0.25
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.8	0.8
Nom. Overall Diameter	mm	4.6	4.8	5.2	6.1	6.6

Electrical Characteristics

BCC Part Number	Unit	C1732	C1734	C1736	C1738	C1740
No of cores x 20AWG (7 x 28)		2	3	4	6	8
Max. DC Resistance Conductor	Ω/km	35.75	35.75	35.75	35.75	35.75
Capacitance conductor to conductor	pF/m	85	80	70	70	70
Nominal Inductance	µH/m	0.5	0.5	0.5	0.5	0.5
Max. Recommended Current at 25°C	Amps	3.75	3.75	3	2.6	2.6
Max. Operating Voltage	Vrms	300	300	300	300	300

Miscellaneous

BCC Part Number	Unit	C1732	C1734	C1736	C1738	C1740
No of cores x 20AWG (7 x 28)		2	3	4	6	8
Operating Temperature	°C			-25 / +75		
Max. Recommended Pulling Tension	N	112	168	224	336	448
Min. Bend Radius (install)	mm	46	48	52	61	66
Nominal Cable Weight	kg/km	27.7	34.5	42.5	59.1	74.4



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.
Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited