

Audio Control & Instrumentation Cable



2 – 3 – 4 – 6 or 8 Cores

20AWG (7 x 28), Flexible Bare Copper, Overall Screen, PVC Sheath

BCC Part No.: C1019 – C1021 – C1023 – C1260 – C1262

Applications

Screened Multi-Conductor cable suitable for Audio, Control, Instrumentation and Building Management Systems (BMS)

Sector - BCC BMS-Tec™

Audio, Control & Instrumentation

Standard References

(BS) EN 50290-2
IEC 60332-1
RoHS directives

Design

1. Conductor

N x Bare Copper wire,
20AWG flexible

3. Drain Wire

24 AWG (7 x 32)
Tinned Copper

2. Insulation

Polyolefin
Core 1: Black
Core 2: Red
Core 3: White
Core 4: Green
Core 5: Brown
Core 6: Blue
Core 7: Orange
Core 8: Yellow

4. Ripcord

Aluminium/Polyester
100% Coverage

6. Sheath Material

Flame-Retardant
Polyvinyl Chloride (PVC)
Standard colour: grey

Standard Put Up Length

305 metres

Physical Characteristics

BCC Part Number	Unit	C1019	C1021	C1023	C1260	C1262
No of cores x 20AWG (7 x 28)		2	3	4	6	8
Nom. Diameter Conductor	mm	1.0	1.0	1.0	1.0	1.0
Nom. Radial Thickness Insulation	mm	0.2	0.2	0.2	0.2	0.2
Nom. Radial Thickness Sheath	mm	0.4	0.4	0.4	0.4	0.4
Nom. Overall Diameter	mm	3.5	3.7	4.1	5.0	5.4

Electrical Characteristics

BCC Part Number	Unit	C1019	C1021	C1023	C1260	C1262
No of cores x 20AWG (7 x 28)		2	3	4	6	8
Max. DC Resistance Conductor	Ω/km	35.75	35.75	35.75	35.75	35.75
Max. DC Resistance Screen	Ω/km	78.5	78.5	78.5	78.5	78.5
Capacitance conductor to conductor	pF/m	100	90	95	117	105
Capacitance cond. To other cond.+screen	pF/m	200	225	224	220	215
Nominal Inductance	µH/m	0.5	0.5	0.5	0.5	0.5
Max. Recommended Current at 25°C	Amps	5	5	4	3.5	3.5
Max. Operating Voltage	Vrms	300	300	300	300	300

Miscellaneous

BCC Part Number	Unit	C1019	C1021	C1023	C1260	C1262
No of cores x 20AWG (7 x 28)		2	3	4	6	8
Operating Temperature	°C	-25 / +75	-25 / +75	-25 / +75	-25 / +75	-25 / +75
Max. Recommended Pulling Tension	N	112	168	224	336	448
Min. Bend Radius (install)	mm	35	37	41	50	55
Nominal Cable Weight	kg/km	22	28.5	35.4	49.9	62.9

Disclaimer: Uncontrolled when printed. Great effort is made to ensure the accuracy of the information presented.
Specification and availability should be confirmed with a call to our sales representatives.