

BCC BMS-Tec™ - LonWorks Cables

1 or 2 Pairs

22AWG, Solid Bare Copper, Individually Screened or No Screen, HFFR Sheath

BCC Part No: C1346 – C1347 – C1348 – C1349



Applications

LonWorks
Interface Bus systems

Sector

BCC BMS-TEC™

Standard References

IEC 60332-1
IEC 60332-3-24 RoHS
directives
(BS)EN 50290
IEC 61034
IEC 60754-1 & 2

Design

1. Conductor

Solid Bare Copper
22 AWG (0.64 mm)

2. Insulation

Solid PE or
Foam PE

3. Lay Up

Two wires twisted
to a pair

4. Drain Wire (if applicable)

24 AWG (0.5 mm)
Tinned Copper

5. Screen (if applicable)

Each pair individually
screened with an
Aluminium/Polyester foil
100% Coverage

6. Cable Core

one pair or two pairs stranded

7. Sheath Material

Halogen-Free (HFFR))
Standard colour: Violet

Standard Put Up Length

305 metres



Physical Characteristics

BCC Part Number	Unit	C1346	C1347	C1348	C1349
Number of pairs		1	2	1	2
Nom. Diameter Conductor	mm	0.64	0.64	0.64	0.64
Insulation material		PE	PE	Foam PE	Foam PE
Nom. Radial Thickness Insulation	mm	0.24	0.24	0.45	0.45
unscreened pair(s)		1	2		
Individually screened pair(s)				1	2
Nom. Radial Thickness Sheath	mm	0.6	0.6	0.6	0.6
Nom. Overall Diameter	mm	3.5	5.2	4.6	7.6

Electrical Characteristics

BCC Part Number	Unit	C1346	C1347	C1348	C1349
No of pairs x 22AWG		1	2	1	2
Nominal Impedance	Ω	100	100	100	100
Max. DC Resistance Conductor	Ω/km	61	61	61	61
Max. DC Resistance Screen	Ω/km			78.5	78.5
Capacitance conductor to conductor	pF/m	46	46	46	46
Capacitance cond. To other cond.+screen	pF/m	76	76	90	80
Max. Recommended Current at 25°C	0.6	2.5	2.5	2.5	2.5
Max. Operating Voltage	Vrms	300	300	300	300

Miscellaneous

BCC Part Number	Unit	C1346	C1347	C1348	C1349
No of pairs x conductor AWG size		1	2	1	2
Operating Temperature	°C	-25 / +75	-25 / +75	-25 / +75	-25 / +75
Max. Recommended Pulling Tension	N	50	100	50	100
Min. Bend Radius (install)	mm	70	104	92	152
Weight	kg/km	17.1	27.7	24.2	56.1



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.
Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited