

BCC Security-Tec™ - Coaxial Cables For CCTV and Video



RG-59, RG-6 and RG-11

Sweep Tested 1 ~ 3000 MHz 75 Ohm Coaxial Cables for CATV and SMATV

BCC Part No: C1025 – C1026 – C1027

Applications

CATV and SMATV

Operating Temperature

-25 to +75 °C

Max. Operating Voltage

300 Vrms

Sector

BCC-Security-TEC™

Coaxial Cables

Standard References

IEC 61196

(BS) EN 50117

(BS) EN 50290-2

RoHS directives

Design

1. Conductor

Solid Copper Covered Steel

(CCS)

2. Dielectric

Foamed Polyethylene

3.Screen

Bonded Aluminium/ Polyester foil

100% coverage

4. Braid

Aluminium

5. Sheath Material

Polyvinyl Chloride (PVC)

Standard Put Up Length

305 or 500 metres



Physical Characteristics

Coax Cables for CATV and SMATV		RG-59 3000 MHz	RG-6 3000 MHz	RG-11 3000 MHz
BCC Part Numbers		C1025	C1026	C1027
Nom. Diameter Conductor	mm	0.81	1.02	1.63
Nom. Diameter Dielectric	mm	3.71	4.60	7.11
Nom. Overall Diameter	mm	6.0	6.8	10.0
Coverage Braid	%	54	60	61
Max. Recommended Pulling Tension	N	350	560	1157
Min. Bend Radius (Install)	mm	60	68	100
Nom. Cable Weight	kg/km	32.42	41.32	86.6

Electrical Characteristics (at 20°C)

Coax Cables for CATV and SMATV		RG-59 3000 MHz	RG-6 3000 MHz	RG-11 3000 MHz
BCC Part Numbers		C1025	C1026	C1027
Impedance	Ohm	75 ± 3	75 ± 3	75 ± 3
Max. DC Resistance Conductor	Ω/km	146.5	92.2	36.5
Max. DC Resistance Screen	Ω/km	52	30	25
Nominal Capacitance	pF/m	53	53	53
Nominal Inductance	μH/m	0.32	0.32	0.32
Velocity of Propagation	%	83	83	83
Nominal Time Delay	ns/m	3.94	3.94	3.94
Min. Return Loss 1 to 1000 MHz	dB	20	20	20
Min. Return Loss 1000 to 2000 MHz	dB	18	20	20
Min. Return Loss 2000 to 3000 MHz	dB	16	20	20

Nominal Attenuation in dB/100m

MHz	5	10	50	100	200	400	550	870	1250	1750	2150	2500	3000
RG-59	2.92	3.45	5.40	8.21	12.56	16.01	19.36	24.74	30.62	36.71	40.82	44.72	48.64
RG-6	2.2	2.48	5.15	6.6	9.56	13.12	15.45	19.69	24.25	29.26	32.88	35.88	39.83
RG-11	1.25	2.03	3.75	5.01	6.85	7.05	9.65	12.6	16.66	20.28	22.93	25.12	28.08



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.

Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited