

BCC Security-Tec™ - Coaxial Cables For CCTV and Video

RG-6, RG-11 and RG-59, Solid Conductor
75 Ohm HFFR Coaxial Cables for CCTV and Video
BCC Part No: C1428 – C1429 – C1430



Applications
CCTV and Video

Operating Temperature
-25 to +75 °C

Installation Temperature
-5 °C (Outdoor Limit)

Max. Operating Voltage
300 Vrms

Standard References

IEC 61196
(BS) EN 50117
(BS) EN 50290-2
IEC 60332-3-24 (Fire Retardant)
IEC 61034 (Low Smoke)
RoHS directives

Design

1. Conductor
Solid Bare Copper (BC)

2. Dielectric

Foamed Polyethylene

3. Braid

Bare Copper

4. Sheath Material

PVC - Cream Halogen-Free
(HFFR)

Standard Put Up Length

305 or 500 metres



Physical Characteristics

Coax Cables for CCTV and Video		RG-59 Solid Conductor	RG-6 Solid Conductor	RG-11 Solid Conductor
BCC Part Numbers		C1428	C1429	C1430
Nom. Diameter Conductor	mm	0.81	1.02	1.63
Nom. Diameter Dielectric	mm	3.71	4.60	7.11
Nom. Overall Diameter	mm	6.0	6.8	10.0
Coverage Braid	%	95	95	90
Max. Recommended Pulling Tension	N	220	310	640
Min. Bend Radius (Install)	mm	60	68	100
Weight	kg/km	48.5	58.2	120

Electrical Characteristics (at 20°C)

Coax Cables for CCTV and Video		RG-59 Solid Conductor	RG-6 Solid Conductor	RG-11 Solid Conductor
BCC Part Numbers		C1428	C1429	C1430
Impedance	Ohm	75 ± 3	75 ± 3	75 ± 3
Max. DC Resistance Conductor	Ω/km	33.5	21.5	8.8
Max. DC Resistance Screen	Ω/km	10.1	10.8	6.5
Nominal Capacitance	pF/m	53.5	53.5	52.8
Nominal Inductance	μH/m	0.32	0.32	0.32
Velocity of Propagation	%	83	83	84
Nominal Time Delay	ns/m	3.97	3.97	3.97
Min. Return Loss 1 to 1000 MHz	dB	20	20	20

Nominal Attenuation in dB/100m

MHz	5	10	50	100	200	300	400	450	550	700	750	870	1000
RG-59	1.9	2.95	6.23	8.53	11.81	15.3	16.41	18.92	21.03	22.97	24.8	26.84	27.89
RG-6	1.78	2.36	4.92	6.56	9.51	12.43	13.78	15.14	17.15	18.37	19.73	20.26	21.96
RG-11	0.99	1.51	2.96	4.27	6.23	8.27	9.51	10.31	11.51	13.45	13.95	14.87	17.06



British Cables Company Limited, Delaunays Road, Blackley, Manchester, M9 8FP, United Kingdom

Tel: +44 (0) 161 741 2345 | Fax: +44 (0) 161 795 8393 | Web: www.britishcablescompany.com | Email: info@britishcables.com

Disclaimer: Great effort is made to ensure the accuracy of the information presented, but errors may occur.
Specification and availability should be confirmed with a call to our sales representatives. ©British Cables Company Limited